



1	VBL-
2	VBL-
3	VBL+
4	VBL+
5	NC
6	NC
7	NC
8	RESET
9	SPENB
10	SPCK
11	SPDA
12	B0
13	B1
14	B2
15	B3
16	B4
17	B5
18	B6
19	B7
20	G0
21	G1
22	G2
23	G3
24	G4
25	G5
26	G6
27	G7
28	R0
29	R1
30	R2
31	R3
32	R4
33	R5
34	R6
35	R7
36	HSYNC
37	VSYNC
38	DOTCLK
39	NC
40	NC
41	VDD
42	VDD
43	NC
44	NC
45	NC
46	NC
47	NC
48	NC
49	NC
50	NC
51	NC
52	DEN
53	GND
54	GND

Display Type	IPS/NORMAL BLACK/Transmissive
Display Resolution	240*(RGB)*320
Viewing Direction	FULL
LCD Controller/Driver	ST7272A
Logic Voltage	2.8V
Operation Temperature	-20°C TO 70°C
Storage Temperature	-30°C TO 80°C
Backlight	White LED Backlight(6PCS-WHITE LED) Vf = 18V~20.4V, If =20mA Brightness = 230cd/m2(Typ)
Remark	



REV	Revision content description	Date
01	FIRST ISSUE	2021.11.01



LCD WORLD LIMITED

TOLERANCE(公差)


Mod.Name

LW035CFRN1-02

DESIGNED(structure) DESIGNED(electron) APPROVED

DRAWING NAME

ASSEMBLE



TOLERANCE UNLESS OTHERWISE SPECIFIED	UNIT	DESIGNED(structure)	DESIGNED(electron)	APPROVED	DRAWING NAME
X.X±0.3	mm				ASSEMBLE
X.XX±0.2					